

MORE ROOM. MORE PASSENGERS.

More Fun!

Meet the Onward 6 Passenger, it's everything you already love about Onward - but more! This 6 passenger Personal Transportation Vehicle was specifically engineered with your comfort and safety in mind. And, with the warranty, backing, and support you expect from Club Car, your family can focus on what really matters.

CRAFTED FOR PEACE OF MIND.

4 wheel brake performance that is crafted and engineered for optimal stopping power



Front row under-seat storage tray with multiple compartments

Available in all Onward standard colors, options, upgrades and accessories

The extended body aesthetic parts have been designed for a fully integrated and sleek look









6 PASSENGER ONWORD



CRAFTED FOR COMFORT.

Long, one-piece canopy design that covers the rear facing passengers

Ergonomic grab handles for second row passengers and dual cup holders positioned for easy reach

Front row seat pod purposely engineered to provide ample leg room for second row passengers

Enhanced suspension system for improved handling and performance

DIMENSIONS Dimensions Overall Width Topped Height Untopped Height Wheel Base Front Wheel Track Rear Wheel Track Ground Clearance POWER Power Source Motor Type Horse Power Batteries (qty/type) Key or Pedal Start Battery Charger	GAS 143 in (363.2 cm) 44.5 in (112.9 cm) 73.5 in (186.7 cm) 49.25 in (125.1 cm) 101.1 in (256.8 cm) 37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt Pedal	ELECTRIC 143 in (363.2 cm) 44.5 in (112.9 cm) 73.5 in (186.7 cm) 49.25 in (125.1 cm) 101.1 in (256.8 cm) 37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW)	GAS 148 in (375.9 cm) 51.3 in (130.5 cm) 88.5 in (224.8 cm) 55.1 in (140 cm) 103.2 in (262.2 cm) 40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	ELECTRIC 148 in (375.9 cm) 51.3 in (130.5 cm) 88.5 in (224.8 cm) 55.1 in (140 cm) 103.2 in (262.2 cm) 40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW)
Dimensions Overall Width Topped Height Untopped Height Wheel Base Front Wheel Track Rear Wheel Track Ground Clearance POWER Power Source Motor Type Horse Power Batteries (qty/type) Key or Pedal Start	44.5 in (112.9 cm) 73.5 in (186.7 cm) 49.25 in (125.1 cm) 101.1 in (256.8 cm) 37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt	44.5 in (112.9 cm) 73.5 in (186.7 cm) 49.25 in (125.1 cm) 101.1 in (256.8 cm) 37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW) 3.7 hp	51.3 in (130.5 cm) 88.5 in (224.8 cm) 55.1 in (140 cm) 103.2 in (262.2 cm) 40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	51.3 in (130.5 cm) 88.5 in (224.8 cm) 55.1 in (140 cm) 103.2 in (262.2 cm) 40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp
Overall Width Topped Height Untopped Height Wheel Base Front Wheel Track Rear Wheel Track Ground Clearance POWER Power Source Motor Type Horse Power Batteries (qty/type) Key or Pedal Start	44.5 in (112.9 cm) 73.5 in (186.7 cm) 49.25 in (125.1 cm) 101.1 in (256.8 cm) 37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt	44.5 in (112.9 cm) 73.5 in (186.7 cm) 49.25 in (125.1 cm) 101.1 in (256.8 cm) 37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW) 3.7 hp	51.3 in (130.5 cm) 88.5 in (224.8 cm) 55.1 in (140 cm) 103.2 in (262.2 cm) 40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	51.3 in (130.5 cm) 88.5 in (224.8 cm) 55.1 in (140 cm) 103.2 in (262.2 cm) 40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp
Topped Height Untopped Height Wheel Base Front Wheel Track Rear Wheel Track Ground Clearance POWER Power Source Motor Type Horse Power Batteries (qty/type) Key or Pedal Start	73.5 in (186.7 cm) 49.25 in (125.1 cm) 101.1 in (256.8 cm) 37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt	73.5 in (186.7 cm) 49.25 in (125.1 cm) 101.1 in (256.8 cm) 37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW) 3.7 hp	88.5 in (224.8 cm) 55.1 in (140 cm) 103.2 in (262.2 cm) 40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	88.5 in (224.8 cm) 55.1 in (140 cm) 103.2 in (262.2 cm) 40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp
Untopped Height Wheel Base Front Wheel Track Rear Wheel Track Ground Clearance POWER Power Source Motor Type Horse Power Batteries (qty/type) Key or Pedal Start	49.25 in (125.1 cm) 101.1 in (256.8 cm) 37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt	49.25 in (125.1 cm) 101.1 in (256.8 cm) 37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW) 3.7 hp	55.1 in (140 cm) 103.2 in (262.2 cm) 40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	55.1 in (140 cm) 103.2 in (262.2 cm) 40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp
Wheel Base Front Wheel Track Rear Wheel Track Ground Clearance POWER Power Source Motor Type Horse Power Batteries (qty/type) Key or Pedal Start	101.1 in (256.8 cm) 37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt	101.1 in (256.8 cm) 37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW) 3.7 hp	103.2 in (262.2 cm) 40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	103.2 in (262.2 cm) 40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp
Front Wheel Track Rear Wheel Track Ground Clearance POWER Power Source Motor Type Horse Power Batteries (qty/type) Key or Pedal Start	37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt	37.1 in (94.3 cm) 37 in (93.9 cm) 4.5 in (11.5 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW) 3.7 hp	40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	40.4 in (102.5 cm) 40.25 in (102.2 cm) 7.1 in (18.1 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp
Rear Wheel Track Ground Clearance POWER Power Source Motor Type Horse Power Batteries (qty/type) Key or Pedal Start	37 in (93.9 cm) 4.5 in (11.5 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt	37 in (93.9 cm) 4.5 in (11.5 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW) 3.7 hp	40.25 in (102.2 cm) 7.1 in (18.1 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	40.25 in (102.2 cm) 7.1 in (18.1 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp
Ground Clearance POWER Power Source Motor Type Horse Power Batteries (qty/type) Key or Pedal Start	4.5 in (11.5 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt	4.5 in (11.5 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW) 3.7 hp	7.1 in (18.1 cm) Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	7.1 in (18.1 cm) 48V DC 3.7 hp (2.7kW) rated, Peak 20 hp
POWER Power Source Motor Type Horse Power Batteries (qty/type) Key or Pedal Start	Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt	48V DC 3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW) 3.7 hp	Gas 429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	48V DC 3.7 hp (2.7kW) rated, Peak 20 hp
Power Source Motor Type Horse Power Batteries (qty/type) Key or Pedal Start	429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt	3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW) 3.7 hp	429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	3.7 hp (2.7kW) rated, Peak 20 hp
Motor Type Horse Power Batteries (qty/type) Key or Pedal Start	429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt	3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW) 3.7 hp	429 cc Kohler, Overhead Valve (OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	3.7 hp (2.7kW) rated, Peak 20 hp
Horse Power Batteries (qty/type) Key or Pedal Start	(OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940 One 12-volt	(14.9 kW) 3.7 hp	(OHV) with EFI 14.0 hp (10.3 kW) rated @ 3600	
Batteries (qty/type) Key or Pedal Start	rated @ 3600 RPM per SAE J1940 One 12-volt		, .	
Key or Pedal Start	One 12-volt	(6) 0 14	RPM per SAE J1940	3.7 hp
Key or Pedal Start		(6) 8-volt	One 12-volt	(6) 8-volt
	***	Pedal	Pedal	Pedal
battery Charger	N/A	E.R.I.C. Automatic, 48-volt; UL and CSA listed	N/A	E.R.I.C. Automatic, 48-volt; UL and CSA listed
Speed Controller	N/A	350 Amp, Solid State Controller	N/A	350 Amp, Solid State Controller
Gear Selection	Center Body Mounted FNR	Center Body Mounted FNR	Center Body Mounted FNR	Center Body Mounted FNR
Rear Axle Ratio	Forward 11.47:1 Reverse 15.63:1	12.32:1	"Forward 11.47:1 Reverse 15.63:1"	12.32:1
PERFORMANCE				
Seating Capactity	6	6	6	6
Dry Weight(w/o Batteries)	951		1071	
Curb Weight	980	1284	1101	1402
Vehicle Load Capacity	1200	1200	1200	1200
Outside Clearance Circle	151 in (383.5 cm)	151 in (383.5 cm)	171.9 in (436.6 cm)	171.9 in (436.6 cm)
High Speed (Level Ground)	18 +/-1 mph	18 +/-1 mph	18 +/-1 mph	18 +/-1 mph
Low Speed (Level Ground)	n/a	n/a	n/a	n/a
STEERING SUSPENSION				
Steering	SportDrive™ — Self-compensating double reduction helical rack & pinion	SportDrive™ — Self-compensating double reduction helical rack & pinion	SportDrive™ — Self-compensating double reduction helical rack & pinion	SportDrive™ — Self-compensating double reduction helical rack & pinion
Suspension (front & rear)	Front: Independent A-arms with Hydraulic shocks Rear: Patent pending w/ Track Bar and Automotive Grade Jounce Bumpers	Front: Independent A-arms with Hydraulic shocks Rear: Patent pending w/ Track Bar and Automotive Grade Jounce Bumpers	Front: Independent wide track Double A-arm with Hydraulic shocks Rear: Patent pending w/ Track Bar and Automotive Grade Jounce Bumpers	Front: Independent wide track Double A-arm with Hydraulic shocks Rear: Patent pending w/ Track Bar and Automotive Grade Jounce Bumpers
Brakes	Four wheel mechanical drum	Four wheel mechanical drum	Four wheel mechanical drum	Four wheel mechanical drum
Parking Brake	Foot actuated, 3-position	Foot actuated, 3-position	Foot actuated, 3-position	Foot actuated, 3-position
Wheels & Tires	10" Atlas or Mercury aluminum wheels with 205/55-10 Loadstar Tubless tires	10" Atlas or Mercury aluminum wheels with 205/55-10 Loadstar Tubless tires	10" Atlas or Mercury aluminum wheels on 22x10-10 Kraken tires 14" Atlas or Mercury aluminum wheels on 23x10-14 Kraken tires	10" Atlas or Mercury aluminum wheels on 22x10-10 Kraken tires 14" Atlas or Mercury aluminum wheels on 23x10-14 Kraken tires
BODY & CHASSIS			22.2 2 22 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	35.5 5.1 25.1.3 1 1 1 4 4 6 6 6
Frame	AlumiCore™ — Ladder-style aluminur			

Body & Finish

Front: Painted TPO | Center: Painted High Impact ABS | Rear: Painted Surlyn

Available Body Colors Metallic Pearl Blue, Metallic Jade Green, Metallic Tuxedo Black, Metallic Platinum, Metallic Candy Apple Red, Metallic Glacier, Metallic Beige, Metallic Ocean Teal Available Seat Colors Standard Beige, Standard White, Standard Black, Premium Light Beige, Premium Camello, Premium Off White, Premium Black, Premium Black/Gray, Premium Gray

