CARRYALL 502



Where Our Standards Meet Yours

The Carryall 502, with Club Car exclusive Kohler Command Pro® closed-loop

EFI engine, combines the features you need most to do your best work with the quality, performance, and engineering of our 500 series. No detail was left out to ensure this vehicle works as intuitively and relentlessly as you do.



CARRYALL 502





	ELECTRIC	GASOLINE
ENGINE/MOTOR TYPE	48-volt DC	Kohler EFI, 4-cycle Gas
CONTROLLER	500 Amp - Solid state	N/A
DISPLACEMENT	N/A	429 сс
CYLINDERS	N/A	Single
VALVING	N/A	Overhead cam
COOLING	N/A	Air cooled
HORSEPOWER (RATED)	3.7 hp (2.7 kW) rated, Peak 20 hp (14.9 kW)	14.0 hp (10.3 kW) rated @ 3,600 rpm per SAE J1940
MAX TORQUE	71 ft-Ib (96.2 Nm) rated @ 1,450 rpm	19.91 ft-Ib (27.0 Nm) rated @ 2,400 rpm
LUBRICATION	N/A	Splash lubrication
GOVERNOR	N/A	Ground speed
TRANSMISSION	Direct drive, double reduction helical gear	Continuously Variable Transmission (CVT)
GEAR SELECTION	Forward/Neutral/Reverse	Forward/Neutral/Reverse
GEAR RATIO	12.32:1	11.47:1 forward; 15.63:1 reverse
IGNITION	N/A	Capacitive discharge
BATTERY	Eight 6-volt flooded lead acid	12-volt 500 CCA 105 min reserve
CHARGER	On-board DeltaQ QuiQ (1 kW high frequency)	N/A
HEADLIGHTS	Two 37.5 watt halogen	Two 37.5 watt halogen
FUEL DELIVERY SYSTEM	N/A	Electronic fuel injection (EFI)
FUEL CAPACITY	N/A	5.5 gal (20.8 L)
STEERING MECHANISM	Self-adjusting rack and pinion	Self-adjusting rack and pinion
SUSPENSION (FRONT)	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
SUSPENSION (REAR)	Semi-independent leaf spring with dual hydraulic shocks	Semi-independent leaf spring with dual hydraulic shocks
BRAKES	4-wheel mechanical drum	4-wheel mechanical drum
PARK BRAKE	Foot operated, multi-lock	Foot operated, multi-lock
BODY (FRONT & FINISH)	ArmorFlex® with automotive paint/ clearcoat, aluminum finish	ArmorFlex® with automotive paint/ clearcoat, aluminum finish
BODY (FRAME & REAR)	Aluminum	Aluminum
TIRES (FRONT)	18 x 8.5-8, 6-ply	18 x 10-10, 6-ply
TIRES (REAR)	18 x 8.5-8, 6-ply	18 x 10-10, 6-ply
WHEELBASE	78.1 in (198.3 cm)	78.1 in (198.3 cm)
OVERALL HEIGHT	47.1 in (119.6 cm)	47.1 in (119.6 cm)
OVERALL LENGTH	118 in (299.7 cm)	118 in (299.7 cm)
BED L X W X H (CARGO BOX)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)	44.2 x 47.5 x 10.5 in (112.2 x 120.6 x 26.6 cm)
DIFFERENTIAL GROUND CLEARANCE	4.2 in (10.7 cm)	4.2 in (10.7 cm)
TRACK WIDTH (FRONT)	36.6 in (92.9 cm)	36.6 in (92.9 cm)
TRACK WIDTH (REAR)	39.5 in (100.3 cm)	39.5 in (100.3 cm)
MAX WIDTH (W/O MIRRORS)	50.3 in (127.7 cm)	50.3 in (127.7 cm)
CURB WEIGHT (W/ BATTERIES)	1,393 lb (631.8 kg)	907 lb (411.4 kg)
TOTAL VEHICLE CAPACITY	1,200 lb (544 kg)	1,200 lb (544 kg)
BED LOAD CAPACITY	800 lb (362.8 kg)	800 lb (362.8 kg)
TOWING CAPACITY	1,500 lb (680.3 kg)	1,500 lb (680.3 kg)
COMBINED GROSS VEHICLE CAPACITY	1,500 lb (680.3 kg)	1,500 lb (680.3 kg)
SPEED	5-17 mph (8-27 kph)	15-17 mph (24-27 kph)
TURNING RADIUS	119 in (302.2 cm)	119 in (302.2 cm)
WARRANTY	 4-year limited battery warranty; 3-year limited powertrain/frame; 2-year limited remaining vehicle 	3-year/3,000 hour limited powertrain/frame; 2-year limited remaining vehicle
Visit clubcar.com for more on Carryall's warranty.		

MANAGEMENT LIFE UNINTERRUPTED

The Carryall 502 was expertly designed with your needs in mind. With extra room, and a high-visibility dash, you can now manage and care for your facility without interruption.



Designed for grounds maintenance, landscaping, and sporting fields and facilities.





High-Visibility Dash enhances sight lines for an unobstructed view. *Optional windshield available



Extra-Wide Monsoon Canopy for fast drainage and better water management.



Spacious Interior means plenty of room for equipment and canine crew members.



Console with Standard Dual USB & Multi-Use Cup Caddy keeps devices charged and drinks, radios, and tools secure.